

SDS Priviglaze+ Combined Xray Warning Light Vision Panel

- Drawing reference(s): Refer to plans, Door Type elevations and Door Schedule and complying, unless stated otherwise, with DoH Health Technical Memorandum 58: Internal Doorsets.
- Manufacturer and reference: Specialist Door Solutions Ltd, Unit 1, Bordon Trading Estate, Old Station Way, Bordon, Hampshire, GU35 9HH, sales@specialistdoorsolutions.com, 01420 543222.
- Fire performance: See Door Schedule. Certification: BM Trada Q-mark.
- Acoustic performance: up to 32dB with standard 44mm door core, or 35dB with 54mm door core, or higher acoustic ratings (NFR only) up to 40-42dB available with specialist acoustic core.
- Glazing and Bead details (see door schedule):
 - SDS Priviglaze+ System, with integral 'Hit-and-miss' privacy blinds combined with integral high intensity 12v LED warning light, displaying message and warning symbols for X-Ray or Laser or other customised message.
 - Control Method: Panel to be wired through the door, into 12v supply with feed linked to external control method (On/Off Switch, Surgeons Panel etc).
 - X-Ray Protection if required: Lead Glass available to suit required level of radiation protection.
 - Laser Protection if required: Laser Shielding available to protect against all medical lasers.
 - Size and position of aperture(s): 805x255mm (VPA11) or 408x408mm (VPA10).
 - Bead System: Flush Glazed with no protruding or recessed beading for maximum hygiene control.